

MV-500

■ COMPOSITION

Packing manufactured with cotton threads and impregnated with white fat inside and outside.

This packing general services are hydraulics and low responsibility.

The MV 500 is the cheaper solution in sealability problems in pumps and valves.

Recomended specially for applications in the naval industry in water pumps and valves.

■ PARAMETER

MV-500	Maximum working conditions
TEMPERATURE (°C)	120
PRESSURE (Bar)	10
VELOCITY (m/s)	5
P-H	6-8

■ APLICATIONS

It is indicated for hydraulic services, not only for fresh water but also for seawater.

In valves and pumps in all sort of water applications.

INDUSTRIES:

MARINE.
 PROCESS PLANTS.
 HIDROELECTRIC & HIDRAULIC PLANTS.
 POWER GENERATION PLANTS. MINING.

WATER APPLICATIONS (SEWAGE).
 STEEL & FOUNDRY FACTORIES OTHER



Montero®

FIBRAS Y ELASTOMEROS, S.A.

El Juncal, s/n. Edificio Fuentes 2º Local 11
 48510 Valle de Trapaga, Vizcaya, España.
 Tel. + 34-94 418 00 11 Fax. + 34-94 418 91 83
 e-mail: access@monterofye.com
<http://www.monterofye.com>

The data given on this technical sheet should not be used as applications limits, but as guidance for an appropriate choice. We can offer guarantees only for the quality of our products.

